




# Technical Specifications

	<b>Deco 2000 ATT</b>	<b>Deco 2000 with Bender Plate</b>
<b>Stitch style</b>		
<b>Machine Performance</b>	250 to 300 jackets per 8-hour shift	
<b>Sewing Speed</b>	500 spm	
<b>Stitch Length</b>	0.1 - 7 mm	
<b>Maximum Work Thickness</b>	7 mm	
<b>Recommended Thread Length</b>	cone thread 400 - 900 mm standard	pre-cut wax thread 400 - 1200 mm
	pre-cut wax thread 400 - 1200 mm	
<b>Automatic Thread Trimming</b>		N/A
<b>Recommended Thread</b>	Synthetic thread	N/A
	Silcora Waxed Silk Thread Size A - Lightweight Material Size C - Medium / Heavyweight Material	
<b>Needle</b>	AMF Reece 59 - 83 - 1032 B1 Size 26, 28 - Lightweight material Size 36 - Normal weight material fine thread Size 38 - Normal weight material normal thread Size 49 - Heavyweight material	
<b>Motor</b>	Induction Motor; 0,37 KW	
<b>Electrical Requirements</b>	230 V, 50/60 Hz, 1Ph	
<b>Table Dimensions</b>	956 (L) x 630 (W) x 850	
<b>Machine Head Dimensions</b>	1118 mm (L) x 940 mm (W) x 1118 mm	
<b>Machine Head Weight</b>	220 kg	
<b>Dimensions Packed Weight</b>	1168 mm (L) x 1041 mm (W) x 1118 mm (H) 338 kg	